

WISECO **ATV Pistons**

POLARIS

Model	Bore (mm) x Stroke (mm)	Displ. (cc)	Bore Size (mm)	Over Sizes (mm)	New Wiseco Piston Part No.	Previous Wiseco Piston Part No.	Price Per Piston	Repl. Ring Set <i>See page 109 for \$</i>	Repl. Circlips \$1.00 (D06)	Repl. Wrist Pin	Optional Accessories <i>Bearings & Gaskets are all Top End</i>
POLARIS ATV (2-Stroke)											
Trail Boss 250 4 x 4 Scrambler 250 Trail Blazer 250	72 x 60	244 248 249 251 253 255 258	72 72.5 72.75 73 73.25 73.5 74	STD 0.50 0.75 1.00 1.25 1.50 2.00	536M07200 536M07250 536M07275 536M07300 536M07325 536M07350 536M07400	536PS 536P2 - 536P4 - 536P6 536P8	97.41 (D5485) 107.14 (D8246)	2835CD 2854CD 2864CD 2874CD 2884CD 2894CD 2913CD	CW18	S459	Bearing: B1014 Gasket: W5326 Con. Rod: CR168 Sleeve: FL5168SL
ATV300 1994-00 PRO-LITE	74.5 x 65	283 287 291 295 299	74.5 75 75.5 76 76.5	STD 0.50 1.00 1.50 2.00	721M07450 721M07500 721M07550 721M07600 721M07650	721PS 721P2 721P4 721P6 721P8	98.35 (D1095) 108.19 (D1946)	2933TD 2953TD 2973TD 2992TD 3012TD	CW18	S513	Bearing: B1014 Gasket: W5667 Con. Rod: - Sleeve: FL5273SL
Trail Boss 350	80 x 70	352 356 361 365 370	80 80.5 81 81.5 82	STD 0.50 1.00 1.50 2.00	639M08000 639M08050 639M08100 639M08150 639M08200	639PS 639P2 639P4 639P6 639P8	104.27 (D6526) 114.70 (D2886)	3150TD 3169TD 3189TD 3209TD 3228TD	CW18	S278	Bearing: B1002 Gasket: W5423 Con. Rod: CR169 Sleeve: FL5171SL
ATV 400 thru 2003	83 x 70	378 381 383 386 388 390 393 397	83 83.25 83.5 83.75 84 84.25 84.5 85	STD 0.25 0.50 0.75 1.00 1.25 1.50 2.00	675M08300 675M08325 675M08350 675M08375 675M08400 675M08425 675M08450 675M08500	675PS - 675P2 - 675P4 - 675P6 675P8	100.24 (D4106) 110.26 (D6166)	3268TD 3278TD 3287TD 3297TD 3307TD 3317TD 3327TD 3347TD	CW18	S278	Bearing: B1002 Gasket: W5517 Con. Rod: CR169 Sleeve: 3108FA
POLARIS ATV (4-Stroke)											
500 Xplorer 1996-00 Sportsman 1996-00 Scrambler 1996-00	92 x 75	499 504 509	92 92.5 93	STD 0.50 1.00	4677M09200 4677M09250 4677M09300	4677PS 4677P2 4677P4	138.06 (D4828)	3622XC 3642XC 3661XC	CW23	S591	Gasket: W5747 Con. Rod: - Sleeve: -
10.2:1 Compression											

- 2-stroke pistons are supplied with rings, wrist pins & circlips, unless noted otherwise.
- 4-stroke pistons are supplied with rings, wrist pins & circlips.
- Replacement ring style is stamped on piston dome - Example: "C" for XC, "G" for XG and "H" for XH.

